
CARBINE


The Next Generation in Locking

CNL-MFS-BL/SC/SL NIGHT HAWK METAL FRAME STRIKE

STRIKE INSTALLATION INSTRUCTIONS




1. Close the door and using the lock case as a guide, mark the position to install the strike on the metal jamb.




2. Align the strike mounting plate centrally within the marked horizontal lines, and position the tongue on the strike mounting plate flush with the door jamb.

Mark and secure with four 10G x 1/2" metal screws.



3. Place strike onto strike mounting plate and slide sidewards into position.

Secure with two M5 x 26mm Screw Pins.



4. The installation of the Night Hawk metal frame strike is now complete.

Special Notes:
INWARD OPENING INSTALLATION: Refer to lock installation instructions and template.
OUTWARD OPENING INSTALLATION: Outward opening strike is sold separately, product code CNL-OSSC.
SECURITY: For maximum security, the gap between the lock case and strike should be kept to a minimum and must not exceed 5mm.

WARNING
Please keep contents away from small children. Suffocation Hazard.

NOTE
Please dispose of plastic bags and other packaging in a thoughtful manner

PLEASE RECYCLE

Lock & Key

LOCK & KEY Phone: **1300 652 692** Web: **www.lockn key.com.au** Web: **www. daveweb.com.au**

Distributed in Australia by
LOCK AND KEY a division on the
DAVCOR GROUP PTY LTD ABN 95 003 562 598
Distributed in New Zealand by
BABER LOCK & KEY
This product has been manufactured in Taiwan to Lock and Key Company specifications

This product is guaranteed to be free from defects in materials and workmanship for a period of one (1) year from the date of original purchase. This warranty is for replacement of product only and Lock and Key Company does not accept responsibility for any direct or consequential damage caused by this product or its use. This warranty does not cover damage that results from faulty installation or usage, alteration or modification of the product or tarnishing of the finish including colour change due to weather, salt or chemical. Should this product not perform satisfactorily in its intended application, return it to place of purchase for replacement.